



TT-136 Multispray

AGAINST RUST, DAMP, MOISTURE AND LEAKAGE CURRENTS

- ✓ Superfast acting.
- ✓ Works by cold shrinkage.
- ✓ Colourless and practically odour-free.
- ✓ 360° spray direction.

Technical Info

- Base: mineral oil.
- Colour: colourless.
- Odour: characteristic.
- Water solubility: insoluble.
- Density at 20°C: 0.811.
- Partial pressure: 8,53 bar.
- Boiling point: 187 – 300°C.
- Relative density at 20°C: 0.81g.
- Temperature resistance: -80°C to +190°C.
- Dynamic viscosity at 20°C: 1 mPa.s.
- Kinematic viscosity at 20°C: 1 mPa.s.
- Storage life: 36 months if kept dry, cool and frost-free.
- Safety measures: Please consult the safety card.

Packing

TT-136 Multispray - aerosol 600ml

236116118

Product

Characteristics

- Is fast and effective in contact with rust, tar, grease and water and combines penetrating power, lubrication, protection, cleaning, rust removal, drives away moisture and cold shrinkage, resulting in time saving.
- Contains no silicones and is safe to use on plastics, lacquers ...

Use

- Shake well before use.
- Spray and briefly allow to penetrate.
- If necessary, allow the propellant gasses to evaporate.