

SEAL WITH CONFIDENCE
HVAC TAPES PROS TRUST

YOU RELY ON TAPE TO GET THE JOB DONE QUICKLY AND EFFICIENTLY. THAT'S WHY WE OFFER A FULL PORTFOLIO OF FOIL, FILM AND COMPOSITE HVAC TAPES THAT DELIVER THE PRODUCT FEATURES AND FULL SYSTEM CLOSURE YOU DEMAND. WITH OPTIONS TO MEET THE CODE, PERFORM IN THE COLD AND SEAL A BROAD RANGE OF HVAC MATERIALS, SHURTAPE HAS YOU COVERED WITH THE TAPES YOU NEED TO ENSURE AIRTIGHT PERFORMANCE YOU CAN BE PROUD OF.

DC 181
Shurtape®



UL 181B-FX Listed film tape for use on Class 1 Flex Duct for connecting, joining, sealing and patching flexible air ductwork. DC 181 features an acrylic adhesive system, high performance in temperatures ranging from -10 F to 210 F, and is clearly printed with the UL Listing to ensure every job is code compliant.

LS 300
Shurtape®



UV-resistant line set tape for taping outdoor HVAC components. An economical solution that holds strong outdoors, LS 300 is durable, easy to unwind, and can be applied in a variety of temperature ranges and used in humid conditions.

PW 100
Shurtape®



General purpose, corrosion-resistant PVC tape for use on under and above ground pipe installations. PW 100 pipe wrap tape offers excellent moisture resistance and conformability to protect metal and plastic piping.

EV 57
Shurtape®



General purpose grade, 7 mil vinyl insulating tape for use in a variety of mechanical and electrical applications, including color-coding and phasing tasks. UL Listed and CSA Approved, EV 57 is a highly conformable, lead free and flame retardant electrical tape for use indoors and out.

EV 77
Shurtape®



Professional grade, 7 mil vinyl insulating tape for all-weather insulating and splicing applications, as well as color-coding and phase identification, in temperatures ranging from 0 F to 220 F. UL Listed and CSA Approved, EV 77 electrical tape is lead free, flame retardant and constructed with a specialized PVC backing that contractors demand.

VP 410
Shurtape®



UV-resistant SPVC line set tape used in the HVAC industry to wrap line sets, seam closed cell sponge insulation, and insulate air ducts and underground pipes. VP 410 is engineered with a non-corrosive adhesive and flexible backing; can be used in extensive temperature, moisture and humid conditions; and meets OSHA color-coding requirements.

AF 099
Shurtape®



UL 181 A-P/B-FX Listed aluminum foil HVAC tape for joining and sealing joints, connections and seams on rigid fiberglass ductboard and flexible air duct. A tape that "does it all," AF 099 is engineered to form airtight bonds on joints and seams in temperatures ranging from -20 F to 260 F and in humid conditions.

AF 914CT
Shurtape®



Linered cold temperature aluminum foil tape for joining and sealing aluminum-backed and fibrous insulation and metal ductwork, and to repair metal and sheet metal. Designed with an acrylic adhesive and tested in accordance with UL 723, AF 914CT delivers an airtight seal in temperatures ranging from -20 F to 260 F.

AF 975CT
Shurtape®



Cold temperature aluminum foil tape for use in temperatures ranging from -20 F to 260 F when joining and sealing aluminum-backed or fibrous insulation and metal ductwork, as well as when repairing metal and sheet metal. AF 975CT is linered, designed with an acrylic adhesive, tested in accordance with UL 723 and delivers an airtight seal every time.

AF 984CT
Shurtape®



UL 723 tested Foil/Scrim/Kraft (FSK) tape for sealing seams in scrim-reinforced duct insulation. Ideal for applications that demand maximum strength tape, AF 984CT is linered, offers an acrylic adhesive and can be used in temperatures ranging from -20 F to 260 F.

AF 990CT
Shurtape®



All Service Jacket (ASJ) tape for use in cold and dual temperature systems to seal, seam and join scrim-reinforced pipe and duct insulation. AF 990CT is linered and offers an acrylic adhesive, performs in temperatures ranging from -20 F to 260 F and is tested in accordance with UL 723.

AF 995CT
Shurtape®



All Service Jacket+ (ASJ+) tape for sealing butt joints on ductboard and pipe insulation wrapped with ASJ+ faced backing. Linered and tested in accordance with UL 723, AF 995CT is constructed with a white poly-scrim-foil backing that inhibits mold growth and is DECA free, in addition to an all-weather acrylic adhesive that performs in temperatures ranging from -20 F to 260 F to deliver a permanent solution for use across a range of jobs.

P- 628
Pro Gaff®



Professional grade gaffer's tape used in the HVAC industry. Durable P- 628 offers a combination of excellent holding power, conformability and high tensile strength to get the job done quickly and efficiently.

PC 622
Shurtape®



Premium grade cloth duct tape used for sealing and seaming duct systems in the HVAC industry. PC 622 combines high tensile strength, excellent holding power and conformability to deliver a tape solution that can withstand the rigors of the job.

PC 857
Shurtape®



UL 181B-FX Listed and printed cloth duct tape used to seal, seam and join Class 1 Flex Duct, even when surfaces are rougher or not fully clean. PC 857 offers high adhesion, superior shear strength and excellent tearability, and is recommended for applications that must meet or exceed the strict requirements of UL, flex duct manufacturers and city and state codes.

SF 682
Shurtape®



ShurFLEX® HVAC professional grade metalized cloth duct tape designed for airtight and moisture-free seaming, connecting, splicing, patching and sealing of sheet metal and flex duct, rigid ductboards, air vents, insulation, fibrous filter banks and pollution collection systems. For superior performance, SF 682 is easy to use, hand tearable and designed in color and appearance to match sheet metal, flex duct and ductboard.

PC 6
Shurtape®



PC 6 is a co-extruded utility grade cloth duct tape for non-critical, general use applications, including packaging, bundling, sealing, repairing, holding and waterproofing.

PC 9
Duck Pro®



PC 9 Duck Pro® by Shurtape® is a general purpose, contractor grade cloth duct tape featuring aggressive adhesive and cold temperature performance for sealing, seaming, repairing, holding and waterproofing applications, as well as for tasks in the restoration industry, such as holding poly-sheeting.

PC 621
Duck Pro®



PC 621 Duck Pro® by Shurtape® is a heavy duty cloth duct tape designed for HVAC applications to hold, seal and seam sheet metal and flex duct, exhaust vents and preformed insulation, and can also be used in industrial applications for holding, splicing, protecting and packaging.

PC 618
Duck Pro®



PC 618 Duck Pro® by Shurtape® is a co-extruded professional grade, industrial cloth duct tape for holding, securing, seaming, repairing, bundling, splicing, packaging and masking in HVAC, industrial, commercial, utilities, trucking and automotive applications, and can also be used as a condensation barrier in appliance assemblies.

PC 609
Duck Pro®



PC 609 Duck Pro® by Shurtape® is a professional grade cloth duct tape for use in a variety of industries, including in the HVAC industry to repair thermal insulation and seal metal ductwork; in the manufactured housing industry to seam bottom boards and for patching, seaming and sealing; and general purpose use for packaging, bundling, holding, wrapping and waterproofing.

SF 685
Shurtape®



ShurMASTIC® roll mastic tape for indoor or outdoor use to seal sheet metal and PVC-coated duct in temperatures up to 200 F. SF 685 is a linered, paintable foil tape that's tested in accordance with UL 723 and delivers permanent, airtight and water-resistant seals.

SF 686
Shurtape®



ShurMASTIC® butyl foil tape used for airtight and moisture-free sealing of Class 1 Flex Duct, sheet metal, PVC-coated duct and duct wrap vapor barriers, and is also approved for subgrade application on PVC-coated duct. A paintable, UL 181B-FX Listed mastic on a roll for indoor or outdoor use, SF 686 is designed with a butyl rubber adhesive system that can withstand wide temperature variances once applied.

MJ 100
Shurtape®



Open weave fiberglass mesh tape used for reinforcing joints, seams and connections when paint-on mastic is used in HVAC applications, and can also be applied to drywall seams before the application of joint compound. MJ 100 drywall tape is self-adhering and offers superior strength compared to paper.



LEARN MORE

SHURTAPE.COM
1.888.442.TAPE

Shurtape
TECHNOLOGIES

ISO 9001 CERTIFIED QUALITY SYSTEM © Shurtape Technologies, LLC 2026/MMC 02096
All trademarks are registered trademarks owned by Shurtape Technologies, LLC, unless otherwise noted.

Tape Solutions for the HVAC Industry



Shurtape
INDUSTRIAL